



11-03-2016

**TUBO FLESSIBILE A ONDE PARALLELE STANDARD -- AISI 321  
ROTOLI O BARRE 6 MT -- MONOPARETE**

CODICE	ARTICOLO	Ø interno ± 0,3 mm	Ø esterno ± 1 mm	Spessore	Raggio curvatura statico (mm)	Raggio curvatura dinamico (mm)	Pressione esercizio bar	Passo mm.		
380.02.002	TOP 12	12,2	17,0	0,15	30	135	3,0	3,00		
380.02.003	TOP 16	16,2	21,2	0,15	24	185	3,0	3,60		
380.02.004	TOP 20	20,4	27,0	0,15	50	210	2,0	3,70		
380.02.005	TOP 25	25,2	32,3	0,20	65	245	2,0	3,70		
380.02.006	TOP 32	32,3	42,0	0,25	75	265	1,5	4,50		
380.02.007	TOP 40	40,3	51,0	0,25	95	315	1,5	5,80		
380.02.018	TOP 45	45	57	0,25	105	330	1,5	5,80		
380.02.008	TOP 50	50,4	62,0	0,25	125	355	1,0	5,80		
380.02.017	TOP 60	60	73	0,25	135	390	1,0	5,80		
380.02.009	TOP 65	64,9	78,0	0,25	170	445	1,0	7,50		
380.02.016	TOP 76	76,3	92,0	0,30	185	485	1,0	9,50		
380.02.010	TOP 80	80,4	98,0	0,30	195	495	1,0	9,50		
380.02.011	TOP 100	100,2	118,0	0,30	245	595	1,0	11,00		
380.02.012	TOP 125	125	145	0,30	280	660	0,6			
380.02.019	TOP 150	152	175	0,30	320	815	0,6			
380.02.020	TOP 200	198	235	0,30	435	1015	0,6			
380.02.021	TOP 250	250	280	0,30	550	1220	0,6			
380.02.022	TOP 300	300	330	0,30	650	1420	0,6			

Descrizioni e caratteristiche tecniche indicative e non impegnative